

4-1/2" SJS™II HIGH-POWER ANGLE GRINDER, PADDLE SWITCH



NEW TOOL OVERVIEW GA4595



FEATURES

- Powerful 15.0 AMP motor delivers more output and 11,500 RPM
- SJS™II provides a leaf spring and cam gear drive mechanism that is engineered to reduce vibration for increased operator comfort during extended use
- Vibration absorbing side handle provides increased comfort on the job
- Electronic Controller provides constant speed control which automatically applies additional power to the motor to maintain speed under load
- Electronic Controller provides soft start which is designed to suppress start-up reaction for smooth start-ups and longer gear life
- Electronic Controller provides an electronic current limiter which helps protect the motor from overload in high torque applications
- Labyrinth construction seals and protects the motor and bearings from dust and debris for longer tool life
- Motor fan is designed with enlarged fins for increased air flow and a cooler running motor

SPECIFICATIONS

Wheel Diameter	4-1/2"
AMPS	15
Spindle Type	5/8" - 11 UNC
Lock-On Switch	Yes
Lock-Off Switch	No
Switch Type	Body grip/paddle
Overall Length	12-7/8"
Variable speed dial	Yes
Net Weight	5.7 lbs.
Shipping Weight	9.17 lbs.
UPC Code	088381-771696

STANDARD EQUIPMENT

- 4-1/2" SJS™II High-Power Angle Grinder, Paddle Switch (GA4595)
- 4-1/2" Grinding Wheel (A-95956)
- 4-1/2" Tool-less Wheel Guard (135107-4)
- Lock Nut (193465-4)
- Lock Nut Wrench (782424-9)
- Inner Flange (224399-1)
- Side Handle (153489-2)

PRODUCT HIGHLIGHTS



POWER

Powerful 15.0 AMP motor delivers more output and 11,500 RPM



COMFORT

SJS™II technology is a leaf spring and cam gear drive mechanism engineered to reduce vibration



DURABILITY

Zig-zag epoxy is applied to the armature for protection from debris and longer tool life



VERSATILITY

Labyrinth construction seals and protects the motor and bearings from dust and debris

RELATED PRODUCTS

1. 4-1/2" Clip-On Cut-Off Wheel Guard Cover (199709-0)
2. 4-1/2"-5" Dust Extraction Surface Grinding Shroud (195236-5)
3. 5" Dust Extraction Tuck Point Guard (196846-1)
4. 4-1/2" - 5" Dust Extraction Cutting Guard (198415-4)
5. 4-1/2" - 5" Dust Extraction Cutting Guard (193794-5)

